



GLIDEROL GARAGE DOORS Rol•a•matic **GR II**[®]

Roller Door Retrofit
Remote Control Operator



Rol•a•matic GR II[®]

The Rol•a•matic GR II[®] Operator is a quiet, smooth and reliable operator which can be found in many countries world wide. Comprising of the most up-to-the-minute technology, the Rol•a•matic GR II[®] operator is a must for any home with a roller door.

Convenience, Safety and Security

Homeowners worldwide are becoming increasingly aware that an automatic Roller Door operator is something that you cannot do without. This operator when installed on a Roller Door will provide you with convenience you can rely on at the press of a button with your Glide-a-code[®] handset. Gone are the days of getting out of your car at night or in the rain, the Rol•a•matic GR II[®] operator with its numerous safety and security features will see to this.

Value for Money

The Rol•a•matic GR II[®] includes everything to convert a manual Roller Door to automatic remote control. A powerful motor and drive unit with a manual or automatic operation selector, a Glide-a-Code[®] radio transmitter handset to operate your door from inside the car, a wall mounted control inside the garage containing a radio receiver, sophisticated electronics, an automatic light and a push button control for door operation inside the garage.

Quick and Trouble Free Installation

The Rol•a•matic GR II[®] is a separate operator which, subject to power availability, easily converts existing manual Roller Doors to automatic remote control. Installation to an existing Roller Door is quick and easily done in a matter of minutes.

Gliderol Garage Doors
A Division of Gliderol
International Pty Ltd
ACN 007 928 949

Gliderol Garage and
Industrial Doors Ltd
Davy Drive
North West Industrial Estate
Peterlee
Co. Durham SR8 2JF

Telephone: 0191 518 0455
Facsimile: 0191 518 0548
Web: www.gliderol.co.uk
E-mail: info@gliderol.co.uk

Rol•a•matic GR II[®]
Roller Door Retrofit
Remote Control Operator

The Company reserves the right to make changes or improvements to the products or accessories without notice and without incurring any obligation to make similar changes or improvements to goods previously ordered.

Rol•a•matic GR II® Remote Control Operator



Rol•a•matic GRII® Advantages

Drive Unit. Is housed within the door roll, if your Roller Door has limited side room on either side of the Roller Door, the Rol•a•matic GRII® is the only operator to suit your situation.

Low Maintenance. Rol•a•matic GRII® uses a hard-wearing nylon gear mechanism, which will ensure long life with limited maintenance and no lubrication required.

Quiet Operation. As the drive unit is housed within the door roll, noise emissions are substantially reduced, resulting in a quiet and smoother performance.

Simple Push Button. Either by hand held Glide-a-Code® transmitter or wall mounted push button. The unique rolling code circuitry ensures fail-safe security and eliminates the risk of another handset using the same code.

Side Room. No additional side room is required as the Rol•a•matic GRII® is designed to recess partly within the door roll.



ABOVE: Two nylon location forks are used to engage the Roller Door to the Rol•a•matic GRII® operator.

IMPORTANT

The roller door should be in good working order and condition. Some adjustments may be necessary for the Rol•a•matic II operator to be totally effective.

Verify with your installer that the Rol•a•matic GRII® operator is compatible with the size of your door.

Able to be fitted to most brands of Roller Door easily and effectively. It is important to note that the door does not have to be removed to allow installation of the Rol•a•matic GR II®

Rol•a•matic GR II® Features

Safety Reversing. The drive unit automatically reverses should the downward movement of the door be restricted.

Security Coded. The Glide-a-Code® transmitter, uses a UHF radio frequency that after each transmission the handset and control box roll to a new window within a combination range of over 2 billion codes. The Glide-a-Code® handset is one of the most secure in the world market and will ensure you that your Rol•a•matic GRII® operator will not be activated by another transmitter. Miniscule in size the Glide-a-Code® handset can operate up to three remote Roller Doors and fits neatly onto a keyring.

Low Voltage The wall mounted control box is fully insulated and approved. The operative voltage is a safe low 24 volts (a 3 pin 240V (13 amp) power point is required).

Manual Conversion In the event of power failure, simply moving one switch allows you to use the door manually.

Automatic Light Illuminates your garage for up to five minutes after the Rol•a•matic GRII® is activated. Enables you to drive into an illuminated garage at night.



Control Box and Push Button

The door can easily be operated using the button on the wall mounted control box.

Optional Extras

Additional Transmitters. Extra transmitters can be purchased on request. You can use up to ten additional transmitters on each Rol•a•matic GRII® unit.

Dual Override. Strongly recommended when alternative access to garage is not available. Used to key operate your Rol•a•matic GRII® operator or engage manual operation in case of power failure.



Dual Override

Intruder Alarm. A local safety alarm can be fitted alongside the control box and will sound continuously whilst door is in travel.

External Lighting A small interface board will enable the owner to activate low voltage lighting when the door is activated.

Rol•a•matic GRII® Guarantee
Each newly installed or retrofitted Rol•a•matic GRII® is guaranteed with the Gliderol exclusive 24 warranty which provides you with a 24 month warranty on all electrical components and mechanical parts.



GLIDEROL
GARAGE DOORS

A Division of Gliderol
International Pty Ltd
ACN 007 928 949
An Australian
Manufacturing Company